



# VF Vision Finish 1K

## Waterborne Finish



- **100% Polyurethane Finish**
- **Very Easy to Use**
- **Non-Yellowing**

- **Residential Use**
- **No Waste or Mixing**
- **Great Leveling**

### Product Description

Forteko Vision Finish 1K is a 100% Polyurethane Waterborne Wood Floor Finish. Vision Finish 1K is low in VOCs, and features a fast drying and curing time. It offers exceptional flow, leveling, and is non-yellowing. The finish is a durable, making it ideal for light commercial, residential, and other trafficked areas. Vision Finish 1K is intended for indoor use only.

### Directions for Use

To prepare the floor, sand it thoroughly according to industry standards, such as NWFA. Ensure the temperature of the room, floor, and Vision Finish 1K is maintained between 65°F and 80°F, with relative humidity between 40% and 60%. Shake the container for 60 seconds before opening, then allow it to rest for 2-3 minutes before applying.

### Specifications

Color	White/Clear
Odor	Non-Offending
Dry Time	1-2 hours; depending on humidity and temperature
Cure Time	5 Days; depending on humidity and temperature
Application Tools	Roller, T-Bar, pad, brush
Unit Size	1 Gallon
Clean Up	Water

Ideal Conditions	Apply between 65°F-80°F with humidity below 65%
Solids	38%
Shelf Life	12 Months
Clarity	Clear
Leveling	Exceptional
Coverage	450-550 sq. ft.



## Application

**For New or Sanded floors:** Vision Finish 1K can be applied using a lightweight T-bar applicator, roller, or brush. For best results on bare, unstained wood floors, use Vision Finish 1K with Forteko primers like Fast Sealer, Clear Sealer and Nature Sealer, following label instructions. Then apply 2-3 coats of Vision Finish 1K finish at a rate of 450-550 sq. ft. per gallon. Apply the first coat evenly on the floor using a lightweight T-bar applicator, roller, or brush, and allow it to dry for 1-2 hours. Abrade between coats if necessary, vacuum all dust, and tack with a lightly water-dampened cloth. Allow the floor to dry completely. If applying a second coat within 12 hours, abrading is not required for adhesion. For previously finished or factory-prefinished floors, apply 1-2 coats of Vision Finish 1K at a rate of 450-550 sq. ft. per gallon, testing adhesion on a small area before recoating the entire floor. Prepare and deep clean the floor using Forteko Prep, following the label instructions. Apply the first coat evenly with a lightweight T-bar applicator, roller, or brush, and allow it to dry for 1-2 hours. Abrade between coats if necessary, then vacuum all dust and tack with a lightly water-dampened cloth. Allow the floor to dry completely. If applying a second coat within 12 hours, abrading is not needed for adhesion.

## For a Screen or Recoat Process

Confirm the floor is free of grease, oil, and dirt. Once done, screen the floor with a No. 180 grit screen. Do not apply Fusion 1k over surfaces previously finished with shellac, lacquer, wax, or stains containing stearates. Then, apply the Fusion 1K using the same method as for new floors.

## Advantages

### Incredibly Easy to Use with No Mixing Required

Vision 1K is designed for effortless application—no hardener, no mixing, and no wasted product. It's ideal for professionals and DIYers alike, offering a more user-friendly experience compared to other finishes like Fusion 1K. Simply shake, rest, and apply—it's that easy.

### Durable, Non-Yellowing Protection for Residential Spaces

Made with 100% polyurethane, Vision 1K delivers long-lasting protection suitable for residential and light commercial use. Its non-yellowing formula preserves the natural beauty of wood floors over time, ensuring a clean and consistent look. Whether you choose matte, satin, or semi-gloss, your floors stay clear and bright.

### Smooth Application with Quick Dry Time

Vision 1K features excellent flow and leveling, making it easy to achieve a smooth, professional-grade finish with minimal effort. It dries in just 1–2 hours, allowing for multiple coats in a single day. The result is a sleek, even surface that's ready for foot traffic in no time.

## Important Notes

Floors previously treated with wax, polish, or oil must be sanded down to bare wood before recoating. Always test Vision Finish 1K on a small area before full application to ensure compatibility and desired results. Follow the flooring manufacturer's advice or contact Forteko Technical Service or your local distributor for more information.