



# UWS Universal Wood Sealer

## Alcohol Sealer



- Dries in 30-45 min in most climates
- Able to screen and hotcoat
- Extremely high build
- Very easy to apply
- Compatible with all Forteko finishes
- Can be applied over stain

### Product Description

Forteko Universal Wood Sealer is ideal for prepping wood flooring surfaces. It works as an undercoat, pre-stain sealer, or wood conditioner. Its wax-free formula makes it compatible with all Forteko Clear Topcoats. Forteko Universal Wood Sealer dries in 30-45 minutes and can be buffed or coated directly over the top in 60 minutes.

### Specifications

Color	Clear Drying; Ambering over time
Odor	Decent
Dry Time	30-45 min
Hotcoat/Sanding Time	60 min
Application Tools	Roller, T-Bar, pad, brush
Coverage	400-500 sq.ft.
Ideal Coverage	Apply between 55°F-90°F with humidity below 85%
Solids	52%

Shelf Life	18 months
Clarity	Clear
Leveling	Exceptional
Unit Size	1 Gallon & 5 Gallon
Clean-Up	Mineral Spirits
Coats	Apply 1 to 2 coats, buffing is optional, a second coat enhances depth on porous woods. You are able to finish coat with water-based or oil-based finishes, 180g buff between coats is ideal.

### Advantages

#### Fast Drying and Quick Recoat Time

Forteko Universal Wood Sealer dries in just 30-45 minutes under most climate conditions. You can screen or apply a hotcoat as soon as 60 minutes after application, saving valuable jobsite time. This rapid turnaround allows for faster project completion and greater efficiency.

#### Highly Versatile and Compatible

This sealer works as an undercoat, pre-stain sealer, or wood conditioner, making it suitable for a variety of applications. It is fully compatible with all Forteko topcoats, including both water-based and oil-based finishes. You can even apply it directly over stain, making it flexible and job-ready.

#### Easy Application with Superior Build

With exceptional leveling and a high-solids formula, the sealer provides an extremely high build with minimal effort. It's easy to apply using a roller, T-Bar, pad, or brush, ensuring a smooth and uniform coat. Coverage ranges from 400-550 square feet per gallon, delivering excellent value.

